

AMENDMENTS TO THE CLAIMS

1 - 4. (Cancelled).

5. (Currently Amended) ~~The propagation environment notification method in a radio communication system according to Claim 2,~~ A propagation environment notification method in a radio communication system constituted by a radio base station and a radio terminal, comprising:

a first step of sending conditions about a user's area layout from a user terminal to a server via a communication line;

a second step of generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

a third step of sending said radio propagation environment information from said server to said user terminal via the communication line;

wherein said first step comprises: sending a service start command from said user terminal to said server;

sending software for clients of predetermined form to said user terminal from said server receiving said service start command;

of inputting said conditions from said user terminal based on said software for clients; and

sending said conditions from said user terminal to said server;

wherein inputting said conditions is comprised of:

performing input and editing of user conditions (said user's area appliance placement information and said radio base station information);

making a determination on whether or not said user's conditions are correctly inputted;

making a determination on completion of said input of conditions, and converting said input conditions into formats capable of being used on said server's part.

6. (Cancel)

7. (Currently amended) ~~The propagation environment notification method in a radio communication system according to Claim 6, A propagation environment notification method in a radio communication system constituted by a radio base station and a radio terminal, comprising:~~

a first step of sending conditions about a user's area layout from a user terminal to a server via a communication line;

a second step of generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

a third step of sending said radio propagation environment information from said server to said user terminal via the communication line;

wherein said first step comprises: sending a service start command from said user terminal to said server;

sending software for clients of predetermined form to said user terminal from said server receiving said service start command;

of inputting said conditions from said user terminal based on said software for clients; and

sending said conditions from said user terminal to said server.

wherein said software for clients comprises:

processing of obtaining said conditions;

processing of converting said conditions into formats capable of being used in processing on said server's part; and

format conversion and display processing for presenting to the user said radio propagation environment information obtained through the processing on said server's part;

wherein said software for clients comprises:

an editor portion for said processing of obtaining conditions; and

a display portion for said display processing;

wherein said editor portion has a function of having appliance placement specific of each user and so on inputted from said user terminal and converting user specific information such as said appliance placement into a predetermined format.

8. (Currently amended) The propagation environment notification method in a radio communication system according to Claim ~~6~~7, wherein said display portion has a function of having said radio propagation environment information displayed on said user terminal.

9. (Previously Presented) The propagation environment notification method in a radio communication system according to Claim 5, wherein said step of performing input and editing of user conditions comprises:

dividing the appliance in said appliance placement information into predetermined shapes; and

generating information of the position of said divided appliance.

10. (Original) The propagation environment notification method in a radio communication system according to Claim 9, wherein said position information is three-dimensional information.

11. (Previously Presented) The propagation environment notification method in a radio communication system according to Claim 5, wherein in said input and editing of user conditions step, information of the position in which said radio base station is placed, information of antenna types and information of sending electric power are inputted as said radio base station information.

12. (Cancelled)

13. (Currently amended) ~~The propagation environment notification method in a radio communication system according to Claim 1,~~ A propagation environment notification method in a radio communication system constituted by a radio base station and a radio terminal, comprising:

a first step of sending conditions about a user's area layout from a user terminal to a server via a communication line;

a second step of generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

a third step of sending said radio propagation environment information from said server to said user terminal via the communication line

wherein the radio propagation environment information generated in said second step is information obtained from receipt electric power and delay variance information in each observation area in the case of dividing said area into a plurality of observation areas.

14. (Cancelled)

15. (Currently amended) ~~The propagation environment notification method in a radio communication system according to Claim 1,~~ A propagation environment notification method in a radio communication system constituted by a radio base station and a radio terminal, comprising:

a first step of sending conditions about a user's area layout from a user terminal to a server via a communication line;

a second step of generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

a third step of sending said radio propagation environment information from said server to said user terminal via the communication line

wherein said second step is comprised of:

defining the number of observation areas M for an observation area ID that is a variable for identifying observation areas;

using ray tracing to estimate a propagation property in the observation area defined by said observation area ID;

storing the receipt electric power and delay variance equivalent to the result obtained in said forty-second step in propagation property data having an arrangement with said observation area ID as an index;

subtracting 1 from said observation area ID;

making a determination on whether or not said observation area ID is greater than 1; and

making a determination on possibility of communication in each observation area if said observation area ID is smaller than 1 as a result of this determination.

16-19. (Cancelled)

20. (Currently amended) ~~The propagation environment notification system in a radio communication system according to Claim 17, A propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:~~

condition sending means for sending conditions about the user's area layout from a user terminal to a server via a communication line;

information generating means for generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

information sending means for sending said radio propagation environment information from said server to said user terminal via the communication line.

wherein said condition sending means comprises:

start command sending means for sending a service start command from said user terminal to said server;

software sending means for sending software for clients of predetermined form to said user terminal from said server receiving said service start command;

condition inputting means for inputting said conditions from said user terminal based on said software for clients; and

second condition sending means for sending said conditions from said user terminal to said server;

wherein said condition inputting means is constituted by:

inputting/editing means for performing input and edition of user conditions (said user's area appliance placement information and said radio base station information);

determining means for making a determination on whether or not said user's conditions are correctly inputted;

input completion determining means for making a determination on completion of said input of conditions; and

format converting means for converting said input conditions into formats capable of being used on said server's part.

21. (Cancelled)

22. (Currently amended) ~~The propagation environment notification system in a radio communication system according to Claim 21, A propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:~~

condition sending means for sending conditions about the user's area layout from a user terminal to a server via a communication line;

information generating means for generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

information sending means for sending said radio propagation environment information from said server to said user terminal via the communication line;

wherein said condition sending means comprises:

start command sending means for sending a service start command from said user terminal to said server;

software sending means for sending software for clients of predetermined form to said user terminal from said server receiving said service start command;

condition inputting means for inputting said conditions from said user terminal based on said software for clients; and

second condition sending means for sending said conditions from said user terminal to said server;

wherein said software for clients comprises:

an editor portion for said processing of obtaining conditions; and

a display portion for said display processing;

wherein said editor portion has a function of having appliance placement specific of each user and so on inputted from said user terminal and converting user specific information such as said appliance placement into a predetermined format.

23. (Cancelled)

24. (Original) The propagation environment notification system in a radio communication system according to Claim 20, wherein said inputting/editing means comprises:

dividing means for dividing the appliance in said appliance placement information into predetermined shapes; and

position information generating means for generating information of the position of said divided appliance.

25. (Original) The propagation environment notification system in a radio communication system according to Claim 24, wherein said position information is three-dimensional information.

26. (Original) The propagation environment notification system in a radio communication system according to Claim 20, wherein in said inputting/editing means, information of the position in which said radio base station is placed, information of antenna types and information of sending electric power are inputted as said radio base station information.

27. (Cancelled)

28. (Currently amended) ~~The propagation environment notification system in a radio communication system according to Claim 16, A propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:~~

condition sending means for sending conditions about the user's area layout from a user terminal to a server via a communication line;

information generating means for generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

information sending means for sending said radio propagation environment information from said server to said user terminal via the communication line;

wherein the radio propagation environment information generated by said information generation means is information obtained from receipt electric power and delay variance information in each observation area in the case of dividing said area environment into a plurality of observation areas.

29. (Cancelled)

30. (Currently amended) ~~The propagation environment notification system in a radio communication system according to Claim 16,~~ A propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:

condition sending means for sending conditions about the user's area layout from a user terminal to a server via a communication line;

information generating means for generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

information sending means for sending said radio propagation environment information from said server to said user terminal via the communication line;

wherein said information generating means is constituted by:

M defining means for defining the number of observation areas M for an observation area ID that is a variable for identifying observation areas;

propagation property estimating means for using ray tracing to estimate a propagation property in the observation area defined by said observation area ID;

storing means for storing the receipt electric power and delay variance equivalent to the result obtained by propagation property estimating means in propagation property data having an arrangement with said observation area ID as an index;

subtracting means for subtracting 1 from said observation area ID, ID determining means for making a determination on whether or not said observation area ID is greater than 1; and

communication possibility determining means for making a determination on possibility of communication in each observation area if said observation area ID is smaller than 1 as a result of this determination.

31 - 34. (Cancelled)

35. (Currently amended) ~~The user terminal according to Claim 32, A~~
user terminal for use in a propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:

condition sending means for sending conditions about the user's area placement from a user terminal to an object apparatus via a communication line; and
information receiving means for receiving radio propagation environment information for said conditions from said object apparatus via the communication line;

wherein said condition sending means comprises:

start command sending means for sending a service start command from said user terminal to said object apparatus;

condition inputting means for inputting said conditions from said user terminal based on software for clients of predetermined form sent to said user terminal from said object apparatus receiving said service start command; and

second condition sending means for sending said conditions from said user terminal to said object apparatus;

wherein said condition inputting means is constituted by:

inputting/editing means for performing input and edition of user conditions (said user's area appliance placement information and said radio base station information);

determining means for making a determination on whether or not said user's conditions are correctly inputted;

input completion determining means for making a determination on completion of said input of conditions; and

format converting means for converting said input conditions into formats capable of being used on said object apparatus's part.

36. (Cancelled)

37. (Currently amended) ~~The user terminal according to Claim 36, A~~
user terminal for use in a propagation environment notification system in a radio
communication system constituted by a radio base station and a radio terminal,
comprising:

condition sending means for sending conditions about the user's area
placement from a user terminal to an object apparatus via a communication line; and

information receiving means for receiving radio propagation environment
information for said conditions from said object apparatus via the communication line;

wherein said condition sending means comprises:

start command sending means for sending a service start command from
said user terminal to said object apparatus;

condition inputting means for inputting said conditions from said user
terminal based on software for clients of predetermined form sent to said user terminal
from said object apparatus receiving said service start command; and

second condition sending means for sending said conditions from said
user terminal to said object apparatus;

The user terminal according to Claim 32, wherein said software for clients
comprises:

processing of obtaining said conditions;

processing of converting said conditions into formats capable of being
used in processing on said object apparatus's part; and

format conversion and display processing for presenting to the user said
radio propagation environment information obtained through the processing on said
object apparatus's part;

The user terminal according to Claim 33, wherein said software for clients comprises:

an editor portion for said processing of obtaining conditions; and
a display portion for said display processing.

wherein said editor portion has a function of having appliance placement specific of each user and so on inputted from said user terminal and converting user specific information such as said appliance placement into a predetermined format.

38. (Currently amended) The user terminal according to Claim ~~36~~ 37, wherein said display portion has a function of having said radio propagation environment information displayed on said user terminal in a form convenient for the user.

39. (Original) The user terminal according to Claim 35, wherein said inputting/editing means comprises:

dividing means for dividing the appliance in said appliance placement information into predetermined shapes; and

position information generating means for generating information of the position of said divided appliance.

40. (Original) The user terminal according to Claim 39, wherein said position information is three-dimensional information.

41. (Original) The user terminal according to Claim 35, wherein in said inputting/editing means, information of the position in which said radio base station is placed, information of antenna types and information of sending electric power are inputted as said radio base station information.

42. (Cancelled)

43. (Currently amended) ~~The user terminal according to Claim 31, A~~
user terminal for use in a propagation environment notification system in a radio
communication system constituted by a radio base station and a radio terminal,
comprising:
condition sending means for sending conditions about the user's area
placement from a user terminal to an object apparatus via a communication line; and
information receiving means for receiving radio propagation environment
information for said conditions from said object apparatus via the communication line;

wherein the radio propagation environment information generated by said information generation means is information obtained from receipt electric power and delay variance information in each observation area in the case of dividing said area environment into a plurality of observation areas.

44. (Cancelled)

45. (Currently amended) ~~The user terminal according to Claim 31, A~~
user terminal for use in a propagation environment notification system in a radio
communication system constituted by a radio base station and a radio terminal,
comprising:

condition sending means for sending conditions about the user's area
placement from a user terminal to an object apparatus via a communication line; and

information receiving means for receiving radio propagation environment
information for said conditions from said object apparatus via the communication line;

wherein said information generating means is constituted by:

M defining means for defining the number of observation areas M for an
observation area ID that is a variable for identifying observation areas, propagation
property estimating means for using ray tracing to estimate a propagation property in
the observation area defined by said observation area ID;

storing data means for storing the receipt electric power and delay
variance equivalent to the result obtained by propagation property estimating means in
propagation property data having an arrangement with said observation area ID as an
index, subtracting means for subtracting 1 from said observation area ID;

ID determining means for making a determination on whether or not said
observation area ID is greater than 1; and

communication possibility determining means for making a determination
on possibility of communication in each observation area if said observation area ID is
smaller than 1 as a result of this determination.

46- 49. (Cancelled)

48. (Original) The server according to Claim 47, wherein said software for clients comprises:

processing of obtaining said conditions, processing of converting said conditions into formats capable of being used in processing on said server's part; and

format conversion and display processing for presenting to the user said radio propagation environment information obtained through the processing on said server's part.

50. (Currently amended) ~~The server according to Claim 47,~~ A server for use in a propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:

condition receiving means for receiving conditions about the user's area layout from a user apparatus via a communication line; and

information sending means for sending radio propagation environment information for said conditions to said user apparatus via the communication line;

wherein said condition receiving means comprises:

start command receiving means for receiving a service start command from said user apparatus;

software sending means for sending software for clients of predetermined form to said user apparatus after receiving said service start command; and

second condition receiving means for receiving said conditions inputted from said user apparatus based on said software for clients;

wherein the means for inputting said conditions by said user apparatus is constituted by:

inputting/editing means for performing input and edition of user conditions (said user's area appliance placement information and said radio base station information);

determining means for making a determination on whether or not said user's conditions are correctly inputted;

input completion determining means for making a determination on completion of said input of conditions; and

format converting means for converting said input conditions into formats capable of being used on said server's part.

51. (Cancelled)

52. (Currently amended) ~~The server according to Claim 51,~~ A server for use in a propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:

condition receiving means for receiving conditions about the user's area layout from a user apparatus via a communication line; and

information sending means for sending radio propagation environment information for said conditions to said user apparatus via the communication line;

wherein said condition receiving means comprises:

start command receiving means for receiving a service start command from said user apparatus;

software sending means for sending software for clients of predetermined form to said user apparatus after receiving said service start command; and

second condition receiving means for receiving said conditions inputted from said user apparatus based on said software for clients;

wherein said software for clients comprises:

an editor portion for said processing of obtaining conditions; and

a display processing;

wherein said editor portion has a function of having appliance placement specific of each user and so on inputted from said user apparatus and converting user specific information such as said appliance placement into a predetermined format.

53. (Cancelled)

54. (Original) The server according to Claim 50, wherein said inputting/editing means comprises:

dividing means for dividing the appliance in said appliance placement information into predetermined shapes; and

position information generating means for generating information of the position of said divided appliance.

55. (Original) The server according to Claim 54, wherein said position information is three-dimensional information.

56. (Original) The server according to Claim 50, wherein in said inputting/editing means, information of the position in which said radio base station is placed, information of antenna types and information of sending electric power are inputted as said radio base station information.

57. (Cancelled)

58. (Currently amended) ~~The server according to Claim 46,~~ A server for use in a propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:

condition receiving means for receiving conditions about the user's area layout from a user apparatus via a communication line; and

information sending means for sending radio propagation environment information for said conditions to said user apparatus via the communication line;

wherein said radio propagation environment information is information obtained from receipt electric power and delay variance information in each observation area in the case of dividing said area environment into a plurality of observation areas.

59. (Cancelled)

60. (Currently amended) ~~The server according to Claim 46,~~ A server for use in a propagation environment notification system in a radio communication system constituted by a radio base station and a radio terminal, comprising:

condition receiving means for receiving conditions about the user's area layout from a user apparatus via a communication line; and

information sending means for sending radio propagation environment information for said conditions to said user apparatus via the communication line;

wherein said radio propagation environment information is generated by:

M defining means for defining the number of observation areas M for an observation area ID that is a variable for identifying observation areas;

propagation property estimating means for using ray tracing to estimate a propagation property in the observation area defined by said observation area ID;

storing data means for storing the receipt electric power and delay variance equivalent to the result obtained by propagation property estimating means in propagation property data having an arrangement with said observation area ID as an index;

subtracting means for subtracting 1 from said observation area ID;

ID determining means for making a determination on whether or not said observation area ID is greater than 1; and

communication possibility determining means for making a determination on possibility of communication in each observation area if said observation area ID is smaller than 1 as a result of this determination.

61. (Previously Presented) A record medium recording therein a control program of a propagation environment notification method in a radio communication system constituted by a radio base station and a radio terminal, said propagation environment notification method comprising:

- a first step of sending conditions about the user's area layout from a user terminal to a server via a communication line;

- a second step of generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

- a third step of sending said radio propagation environment information from said server to said user terminal via the communication line,

- wherein said first step is comprised of:

- a fourth step of performing input and edition of user conditions (said user's area appliance placement information and said radio base station information);

- a fifth step of making a determination on whether or not said user's conditions are correctly inputted;

- a sixth step of making a determination on completion of said input of conditions;

- a seventh step of converting said input conditions into formats capable of being used on said server's part; and

a condition inputting step of inputting said conditions by said user terminal; and

a control program comprised of these fourth to seventh steps is recorded in said record medium.

62. (Previously Presented) A record medium recording therein a control program of a propagation environment notification method in a radio communication system constituted by a radio base station and a radio terminal, said propagation environment notification method comprising:

a first step of sending conditions about the user's area layout from a user terminal to a server via a communication line;

a second step of generating said user's area radio propagation environment information based on said conditions by said server receiving said conditions; and

a third step of sending said radio propagation environment information from said server to said user terminal via the communication line,

wherein said second step is comprised of:

defining the number of observation areas M for an observation area ID that is a variable for identifying observation areas;

using ray tracing to estimate a propagation property in the observation area defined by said observation area ID;

storing the receipt electric power and delay variance equivalent to the result obtained in said forty-second step in propagation property data having an arrangement with said observation area ID as an index;

subtracting 1 from said observation area ID;

making a determination on whether or not said observation area ID is greater than 1; and

making a determination on possibility of communication in each observation area if said observation area ID is smaller than 1 as a result of this determination, and a control program comprised of these forty-first to forty-sixth steps is recorded in said record medium.

63. (Previously Presented) The propagation environment notification method in a radio communication system according to Claim 1, wherein said radio base station is configured as a plurality of radio base stations, and said second step comprises:

estimating a propagation environment for a radio wave emitted from each of said plurality of radio base stations in said user's area layout to generate individual radio wave propagation environment information;

using said individual radio wave propagation environment information to calculate a signal-to-interference ratio expressed by the ratio between the receipt electric power from targeted said radio base stations and the receipt electric power from non-targeted said radio base stations; and

generating said radio propagation environment information for estimating the possibility of communication in said user's area layout, based on said individual radio wave propagation environment information and said signal-to-interference ratio.

64. (Previously Presented) The propagation environment notification method in a radio communication system according to Claim 63, wherein said step of calculating signal-to-interference ratio comprises:

computing the sum of receipt electric power from non-targeted said radio base stations (total interference voltage); and

computing the ratio between the receipt electric power from targeted said radio base stations and said total interference electric power (signal-to-interference ratio).

65. (Previously Presented) The propagation environment notification method in a radio communication system according to Claim 63, wherein said step of calculating signal-to-interference ratio comprises:

a fourth step of computing the receipt electric power from non-targeted said radio base stations at positions in which targeted said radio base stations are placed, as the interference electric power in targeted base stations; and

a fifth step of computing the ratio between the receipt electric power when targeted said radio base stations receive radio waves sent from respective observation points and the interference electric power in targeted said base stations (signal-to-interference ratio).

66. (Previously Presented) The propagation environment notification method in a radio communication system according to Claim 65, wherein the signal-to-interference ratio obtained in said fourth step or the signal-to-interference ratio obtained in said fifth step, whichever smaller, is defined as a signal-to-interference ratio.

67. (Previously Presented) The propagation environment notification method in a radio communication system according to Claim 63, wherein said step of generating said radio propagation environment information comprises:

computing an interference degradation level based on the throughput threshold value of said radio base stations and said signal-to-interference ratio;

evaluating receipt possibility from estimated values of the receipt electric power and delay variance of radio waves sent from said radio base stations; and
generating said radio propagation environment information for making a determination on receipt properties based on the interference degradation level information obtained in said computing step and the receipt possibility evaluation information obtained in said evaluating step.

68. (Original) The propagation environment notification method in a radio communication system according to Claim 63, wherein a second radio wave emission source different from said radio base station is included as a radio wave emission source in said fifty-first step, and in said fifty-first step, radio waves emitted from said second radio wave emission source are also covered as targets for estimating propagation environments.

69. (Original) The propagation environment notification system in a radio communication system according to Claim 16, wherein said radio base station is configured as a plurality of radio base stations, and said information generating means comprises:

individual radio wave propagation environment information generating means for estimating a propagation environment for a radio wave emitted from each of said plurality of radio base stations in said user's area layout to generate individual radio wave propagation environment information;

signal-to-interference ratio calculating means for using said individual radio wave propagation environment information to calculate a signal-to-interference ratio expressed by the ratio between the receipt electric power from targeted said radio

base stations and the receipt electric power from non-targeted said radio base stations;
and

communication possibility estimating means for generating said radio propagation environment information for estimating the possibility of communication in said user's area layout, based on said individual radio wave propagation environment information and said signal-to-interference ratio.

70. (Original) The propagation environment notification system in a radio communication system according to Claim 69, wherein said signal-to-interference ratio calculating means comprises:

total interference electric power computing means for computing the sum of receipt electric power from non-targeted said radio base stations (total interference electric power); and

signal-to-interference ratio computing means for computing the ratio between the receipt electric power from targeted said radio base stations and said total interference electric power (signal-to-interference ratio).

71. (Original) The propagation environment notification system in a radio communication system according to Claim 69, wherein said signal-to-interference ratio calculating means comprises:

first computing means for computing the receipt electric power from non-targeted said radio base stations at positions in which targeted said radio base stations are placed, as the interference electric power in targeted base stations; and

second computing means for computing the ratio between the receipt electric power when targeted said radio base stations receive radio waves sent from

respective observation points and the interference electric power in targeted said base stations (signal-to-interference ratio).

72. (Original) The propagation environment notification system in a radio communication system according to Claim 71, wherein the signal-to-interference ratio obtained by said signal-to-interference ratio calculating means or the signal-to-interference ratio obtained by said second computing means, whichever smaller, is defined as a signal-to-interference ratio.

73. (Original) The propagation environment notification system in a radio communication system according to Claim 69, wherein said communication possibility estimating means comprises:

interference degradation level computing means for computing an interference degradation level based on the throughput threshold value of said radio base stations and said signal-to-interference ratio;

receipt possibility evaluating means for evaluating receipt possibility from estimated values of the receipt electric power and delay variance of radio waves sent from said radio base stations; and

receipt property determination result generating means for making a determination on receipt properties based on the interference degradation level information obtained by said interference degradation level computing means and the receipt possibility evaluation information obtained by said receipt possibility evaluating means to generate said radio propagation environment information for making a determination on receipt properties.

74. (Original) The propagation environment notification system in a radio communication system according to Claim 69, wherein a second radio wave emission

source different from said radio base station is included as a radio wave emission source in said individual radio wave propagation environment information generating means, and said individual radio wave propagation environment information generating means also covers radio waves emitted from said second radio wave emission source as targets for estimating propagation environments.

75. (Original) The user terminal according to Claim 31, wherein said radio base station is configured as a plurality of radio base stations, and said information receiving means comprises:

individual radio wave propagation environment information generating means for estimating a propagation environment for a radio wave emitted from each of said plurality of radio base stations in said user's area layout to generate individual radio wave propagation environment information;

signal-to-interference ratio calculating means for using said individual radio wave propagation environment information to calculate a signal-to-interference ratio expressed by the ratio between the receipt electric power from targeted said radio base stations and the receipt electric power from non-targeted said radio base stations; and

communication possibility information receiving means for receiving said radio propagation environment information for estimating the possibility of communication in said user's area layout, based on said individual radio wave propagation environment information and said signal-to-interference ratio.

76. (Original) The user terminal according to Claim 75, wherein said signal-to-interference ratio calculating means comprises:

total interference electric power computing means for computing the sum of receipt electric power from non-targeted said radio base stations (total interference electric power); and

signal-to-interference ratio computing means for computing the ratio between the receipt electric power from targeted said radio base stations and said total interference electric power (signal-to-interference ratio).

77. (Original) The user terminal according to Claim 75, wherein said signal-to-interference ratio calculating means comprises:

first computing means for computing the receipt electric power from non-targeted said radio base stations at positions in which targeted said radio base stations are placed, as the interference electric power in targeted base stations; and

second computing means for computing the ratio between the receipt electric power when targeted said radio base stations receive radio waves sent from respective observation points and the interference electric power in targeted said base stations (signal-to-interference ratio).

78. (Original) The user terminal according to Claim 77, wherein the signal-to-interference ratio obtained by said signal-to-interference ratio calculating means or the signal-to-interference ratio obtained by said second computing means, whichever smaller, is defined as a signal-to-interference ratio.

79. (Original) The user terminal according to Claim 75, wherein said communication possibility information receiving means comprises interference degradation level computing means for computing an interference degradation level based on the throughput threshold value of said radio base stations and said signal-to-interference ratio;

receipt possibility evaluating means for evaluating receipt possibility from estimated values of the receipt electric power and delay variance of radio waves sent from said radio base stations; and

radio propagation environment information receiving means for receiving said radio propagation environment information for making a determination on receipt properties based on the interference degradation level information obtained by said interference degradation level computing means and the receipt possibility evaluation information obtained by said receipt possibility evaluating means.

80. (Original) The user terminal according to Claim 75, wherein a second radio wave emission source different from said radio base station is included as a radio wave emission source in said individual radio wave propagation environment information generating means, and said individual radio wave propagation environment information generating means also covers radio waves emitted from said second radio wave emission source as targets for estimating propagation environments.

81. (Original) The server according to Claim 46, wherein said radio base station is configured as a plurality of radio base stations, and said information sending means comprises:

individual radio wave propagation environment information generating means for estimating a propagation environment for a radio wave emitted from each of said plurality of radio base stations in said user's area layout to generate individual radio wave propagation environment information;

signal-to-interference ratio calculating means for using said individual radio wave propagation environment information to calculate a signal-to-interference ratio expressed by the ratio between the receipt electric power from targeted said radio

base stations and the receipt electric power from non-targeted said radio base stations;
and

communication possibility information sending means for sending said radio propagation environment information for estimating the possibility of communication in said user's area layout, based on said individual radio wave propagation environment information and said signal-to-interference ratio.

82. (Original) The server according to Claim 81, wherein said signal-to-interference ratio calculating means comprises:

total interference electric power computing means for computing the sum of receipt electric power from non-targeted said radio base stations (total interference electric power); and

signal-to-interference ratio computing means for computing the ratio between the receipt electric power from targeted said radio base stations and said total interference electric power (signal-to-interference ratio).

83. (Original) The server according to Claim 81, wherein said signal-to-interference ratio calculating means comprises:

first computing means for computing the receipt electric power from non-targeted said radio base stations at positions in which targeted said radio base stations are placed, as the interference electric power in targeted base stations; and

second computing means for computing the ratio between the receipt electric power when targeted said radio base stations receive radio waves sent from respective observation points and the interference electric power in targeted said base stations (signal-to-interference ratio).

84. (Original) The server according to Claim 83, wherein the signal-to-interference ratio obtained by said signal-to-interference ratio calculating means or the signal-to-interference ratio obtained by said second computing means, whichever smaller, is defined as a signal-to-interference ratio.

85. (Original) The server according to Claim 81, wherein said communication possibility information sending means comprises:

interference degradation level computing means for computing an interference degradation level based on the throughput threshold value of said radio base stations and said signal-to-interference ratio;

receipt possibility evaluating means for evaluating receipt possibility from estimated values of the receipt electric power and delay variance of radio waves sent from said radio base stations; and

radio propagation environment information sending means for sending said radio propagation environment information for making a determination on receipt properties based on the interference degradation level information obtained by said interference degradation level computing means and the receipt possibility evaluation information obtained by said receipt possibility evaluating means.

86. (Original) The server according to Claim 81, wherein a second radio wave emission source different from said radio base station is included as a radio wave emission source in said individual radio wave propagation environment information generating means, and said individual radio wave propagation environment information generating means also covers radio waves emitted from said second radio wave emission source as targets for estimating propagation environments.

87. (Previously Presented) The record medium according to Claim 61, wherein said radio base station is configured as a plurality of radio base stations, and said second step comprises:

an eighth step of estimating a propagation environment for a radio wave emitted from each of said plurality of radio base stations in said user's area layout to generate individual radio wave propagation environment information;

ninth step of using said individual radio wave propagation environment information to calculate a signal-to-interference ratio expressed by the ratio between the receipt electric power from targeted said radio base stations and the receipt electric power from non-targeted said radio base stations; and

a tenth step of generating said radio propagation environment information for estimating the possibility of communication in said user's area layout, based on said individual radio wave propagation environment information and said signal-to-interference ratio.

88. (Previously Presented) The record medium according to Claim 87, wherein said ninth step comprises:

an eleventh step of computing the sum of receipt electric power from non-targeted said radio base stations (total interference electric power); and

a twelfth step of computing the ratio between the receipt electric power from targeted said radio base stations and said total interference electric power (signal-to-interference ratio).

89. (Previously Presented) The record medium according to Claim 87 or 88, wherein said ninth step comprises:

a thirteenth step of computing the receipt electric power from non-targeted said radio base stations at positions in which targeted said radio base stations are placed, as the interference electric power in targeted base stations; and

a fourteenth step of computing the ratio between the receipt electric power when targeted said radio base stations receive radio waves sent from respective observation points and the interference electric power in targeted said base stations (signal-to-interference ratio).

90. (Previously Presented) The record medium according to Claim 89, wherein the signal-to-interference ratio obtained in said twelfth step or the signal-to-interference ratio obtained in said fourteenth step, whichever smaller, is defined as a signal-to-interference ratio.

91. (Previously Presented) The record medium according to Claim 87, wherein said tenth step comprises:

an eleventh step of computing an interference degradation level based on the throughput threshold value of said radio base stations and said signal-to-interference ratio;

a twelfth step of evaluating receipt possibility from estimated values of the receipt electric power and delay variance of radio waves sent from said radio base stations; and

a thirteenth step of generating said radio propagation environment information for making a determination on receipt properties based on the interference degradation level information obtained in said seventy-first step and the receipt possibility evaluation information obtained in said seventy-second step.

92. (Previously Presented) The record medium according to Claim 87, wherein a second radio wave emission source different from said radio base station is included as a radio wave emission source in said eighth step, and in said eighth step, radio waves emitted from said second radio wave emission source are also covered as targets for estimating propagation environments.

93. (Original) The propagation environment notification method in a radio communication system according to Claim 13, wherein said receipt electric power and delay variance information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said receipt electric power and delay variance information is also expressed in a visually identifiable form.

94. (Original) The propagation environment notification method in a radio communication system according to Claim 93, wherein said receipt electric power is expressed by brightness information, said delay variance information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

95. (Original) The propagation environment notification method in a radio communication system according to Claim 93, wherein said receipt electric power is expressed by chromaticity information, said delay variance information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

96. (Original) The propagation environment notification method in a radio communication system according to Claim 93, wherein brightness is kept constant and said receipt electric power and delay variance information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

97. (Original) The propagation environment notification method in a radio communication system according to Claim 67, wherein said interference degradation level information and receipt possibility evaluation information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said interference degradation level information and receipt possibility evaluation information is also expressed in a visually identifiable form.

98. (Original) The propagation environment notification method in a radio communication system according to Claim 87, wherein said interference degradation level information is expressed by brightness information, said receipt possibility evaluation information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

99. (Original) The propagation environment notification method in a radio communication system according to Claim 97, wherein said interference degradation level information is expressed by chromaticity information, said receipt possibility evaluation information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

100. (Original) The propagation environment notification method in a radio communication system according to Claim 97, wherein brightness is kept constant and said interference degradation level information and receipt possibility evaluation information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

101. (Original) The propagation environment notification system in a radio communication system according to Claim 28, wherein said receipt electric power and delay variance information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said receipt electric power and delay variance information is also expressed in a visually identifiable form.

102. (Original) The propagation environment notification system in a radio communication system according to Claim 101, wherein said receipt electric power is expressed by brightness information, said delay variance information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

103. (Original) The propagation environment notification system in a radio communication system according to Claim 101, wherein said receipt electric power is expressed by chromaticity information, said delay variance information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

104. (Original) The propagation environment notification system in a radio communication system according to Claim 101, wherein brightness is kept constant and said receipt electric power and delay variance information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

105. (Original) The propagation environment notification system in a radio communication system according to Claim 73, wherein said interference degradation level information and receipt possibility evaluation information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said interference degradation level information and receipt possibility evaluation information is also expressed in a visually identifiable form.

106. (Original) The propagation environment notification system in a radio communication system according to Claim 105, wherein said interference degradation level information is expressed by brightness information, said receipt possibility evaluation information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

107. (Original) The propagation environment notification system in a radio communication system according to Claim 105, wherein said interference degradation level information is expressed by chromaticity information, said receipt possibility evaluation information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

108. (Original) The propagation environment notification system in a radio communication system according to Claim 105, wherein brightness is kept constant and said interference degradation level information and receipt possibility evaluation information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

109. (Original) The user terminal according to Claim 43, wherein said receipt electric power and delay variance information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said receipt electric power and delay variance information is also expressed in a visually identifiable form.

110. (Original) The user terminal according to Claim 109, wherein said receipt electric power is expressed by brightness information, said delay variance information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

111. (Original) The user terminal according to Claim 109, wherein said receipt electric power is expressed by chromaticity information, said delay variance information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

112. (Original) The user terminal according to Claim 109, wherein brightness is kept constant and said receipt electric power and delay variance

information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

113. (Original) The user terminal according to Claim 79, wherein said interference degradation level information and receipt possibility evaluation information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said interference degradation level information and receipt possibility evaluation information is also expressed in a visually identifiable form.

114. (Original) The user terminal according to Claim 113, wherein said interference degradation level information is expressed by brightness information, said receipt possibility evaluation information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

115. (Original) The user terminal according to Claim 113, wherein said interference degradation level information is expressed by chromaticity information, said receipt possibility evaluation information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

116. (Original) The user terminal according to Claim 113, wherein brightness is kept constant and said interference degradation level information and receipt possibility evaluation information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

117. (Original) The server according to Claim 58, wherein said receipt electric power and delay variance information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said receipt electric power and delay variance information is also expressed in a visually identifiable form.

118. (Original) The server according to Claim 117, wherein said receipt electric power is expressed by brightness information, said delay variance information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

119. (Original) The server according to Claim 117, wherein said receipt electric power is expressed by chromaticity information, said delay variance information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

120. (Original) The server according to Claim 117, wherein brightness is kept constant and said receipt electric power and delay variance information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

121. (Original) The server according to Claim 85, wherein said interference degradation level information and receipt possibility evaluation information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said interference degradation level information and

receipt possibility evaluation information is also expressed in a visually identifiable form.

122. (Original) The server according to Claim 121, wherein said interference degradation level information is expressed by brightness information, said receipt possibility evaluation information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

123. (Original) The server according to Claim 121, wherein said interference degradation level information is expressed by chromaticity information, said receipt possibility evaluation information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

124. (Original) The server according to Claim 121, wherein brightness is kept constant and said interference degradation level information and receipt possibility evaluation information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

125. (Original) The record medium according to Claim 62, wherein said receipt electric power and delay variance information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said receipt electric power and delay variance information is also expressed in a visually identifiable form.

126. (Original) The record medium according to Claim 125, wherein said receipt electric power is expressed by brightness information, said delay variance information is expressed by chromaticity information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

127. (Original) The record medium according to Claim 125, wherein said receipt electric power is expressed by chromaticity information, said delay variance information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

128. (Original) The record medium according to Claim 125, wherein brightness is kept constant and said receipt electric power and delay variance information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.

129. (Original) The record medium according to Claim 91, wherein said interference degradation level information and receipt possibility evaluation information is expressed in a visually identifiable form, and said radio propagation environment information corresponding to said interference degradation level information and receipt possibility evaluation information is also expressed in a visually identifiable form.

130. (Original) The record medium according to Claim 129, wherein said interference degradation level information is expressed by brightness information, said receipt possibility evaluation information is expressed by chromaticity information, and

said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

131. (Original) The record medium according to Claim 129, wherein said interference degradation level information is expressed by chromaticity information, said receipt possibility evaluation information is expressed by brightness information, and said radio propagation environment information is expressed as color information obtained from said brightness information and said chromaticity information.

132. (Original) The record medium according to Claim 129, wherein brightness is kept constant and said interference degradation level information and receipt possibility evaluation information is expressed by chromaticity, and said radio propagation environment information is expressed as color information with said brightness kept constant.